

LEI250



LEI250 TOUCH15* + CABINET
STICKER KIT WITH "DESIGN YOUR BREAK" GRAPHIC (OPTIONAL)

LEI250, THE PERFECT COFFEE IN ALL ITS FLAVOUR VARIATIONS

LEI250, automatic vending machine with 250 cups capacity, available in espresso coffee from beans and instant coffee.



LEI250 EASY

USER INTERFACE

- Great modularity with 3 interchangeable user interfaces:
 - Easy:** standard membrane interface, with 20 large buttons.
 - Smart:** touchscreen selection interface, with 20 wide backlit selections.
 - Touch:** interface 15" FULL HD with touchscreen technology able to play multimedia contents.
- 2 buttons for customizable sugar dosage (available only on the Easy and Smart versions).
- Wide 3.5" TFT LCD colour display (available only on the Easy and Smart versions).
- Enlightened cup station.
- Introduction and refund coin system standard.

SPECIFICATIONS

- ELECTRICAL SUPPLY
220-240 Vac - 50/60 Hz
- INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances and the pump.

- POWER SUPPLY
1.80 kW single boiler espresso version
- WATER SUPPLY
Fitting connection = 3/4"
Water pressure = 0.5 – 6.5 bar

TECHNOLOGIES

- Version ES with traditional espresso brewer: espresso coffee made in compliance with Italian tradition.
- Version ESV with variable chamber coffee group : doses from 7 to 14 gr. Guarantees perfect coffee extraction in all flavour variations.

FEATURES

- Great configuration flexibility and wide choice of versions. Automatic with water system supply or with autonomous tank inside the base cabinet.
- Door lock with programmable code.
- Mixers are extractable to make maintenance operations easier.
- Standard serpentine kit for tea.
- Cup dispenser adjustable to various diameters (from 70 to 71 mm) and dispenser for 90 or 105 mm stirrers.
- Standard boiler for Espresso: 1500 W – 150 cc.
- Liquid waste tray: 2.3 liters.
- Switching power supply that guarantees total stability of the instant product dose and complete electric safety protections.

- Standard multi-protocol electronics.
- Compatible with telemetry systems.

PAYMENT SYSTEM

- Compatible with all the payment systems available on the market.
- Machine designed for mounting an Exe or MDB change-giver coin mechanism and CASHLESS systems.

PRODUCT CAPACITY

Coffee beans hopper	1.70 kg (4.25 lt)
Single instant coffee canister	2.2 lt
Double instant coffee canister	4.5 lt
Stirrers 90-105mm	250 pcs.
Cups Ø 70-71	250 pcs.

ACCESSORIES


- Cabinet.
- Autonomous pump kit that can be assembled inside the cabinet.
- Cup sensor kit.
- Kit chip clock.
- Coffee waste tray for 200 pods.
- Conversion kit for 80 diameter cups.
- Sticker kit with "Design your break" graphic.

ENVIRONMENT

- Compatible with paper cups and wooden stirrers.
- Optional: cup sensor kit to reduce the consumption of plastic cups and to deliver a beverage in a mug.
- Energy saving mode to reduce the energy consumption when the machine is in stand by.
- In compliance with **ROHS** and **WEEE**.

LEI250 MODELS	LEI 250 1ES-5 SB EASY STD	LEI 250 1ESV-5 SB EASY STD	LEI 250 1ES-5 SB SMART STD	LEI 250 1ES-5 SB T15 STD	LEI 250 IN-6 SB EASY STD
INTERFACE	EASY	EASY	SMART	TOUCH 15"	EASY
VERSION	coffee beans	coffee beans	coffee beans	coffee beans	instant coffee
TRADITIONAL ESPRESSO COFFEE GROUP (ES)	ES	-	ES	ES	-
COFFEE UNIT WITH VARIABLE CHAMBER GROUP (ESV)	-	ESV	-	-	-
COFFEE BEAN HOPPER	1	1	1	1	-
BOILERS	1	1	1	1	1
INSTANT PRODUCTS CANISTERS (OF WHICH 1 SUGAR)	5	5	5	5	6
DIMENSIONS MM	795H x 510W x 645D / WEIGHT 72 KG CABINET: 853H x 510W x 649D (without wall bracket). Depth including wall bracket 703 mm.				


1. Sugar 2. Decaffeinated 3. Tea
4. Coffee beans 5. Milk 6. Chocolate



COFFEE BEANS

(Valid configuration for version with traditional espresso group + version with variable chamber coffee group ESV)

1. Sugar 2. Coffee 3. Decaffeinated
4. Instant 5. Milk 6. Chocolate



INSTANT COFFEE